## NSN 5305-00-822-3824

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-822-3824 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.625 inches **Fastener Length:** 0.625 inches **Head Style:** Fillister **Head Diameter:** Between 0.292 inches and 0.313 inches **Head Height:** Between 0.156 inches and 0.180 inches Washer Quantity: **Internal Drive Style:** Torque **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 30.0 rockwell c and 40.0 rockwell c **Primary Washer Outside Diameter:** Between 0.283 inches and 0.297 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.040 inches Material: Steel comp 1010 or steel comp 1011 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 **Material Specification:** Aisi/sae assn standard all material responses **Thread Series Designator:** Unf Shelf Life: N/a

No

**Unit Of Measure:** 

Demilitarization:

## NSN 5305-00-822-3824

Assembled Washer Screw - Page 2 of 2



Fiig:

A003b0