# NSN 5305-00-822-4523

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-822-4523



## **Thread Class:**

3a

**Thread Direction:** 

Right-hand

#### Thread Length:

Between 1.546 inches and 1.608 inches

#### Fastener Length:

Between 1.688 inches and 1.750 inches

#### **Head Style:**

Flat countersunk

#### Head Diameter:

Between 0.332 inches and 0.385 inches

#### Internal Drive Style:

Cross recess type 1

#### Thread Diameter:

0.190 inches

#### Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

125000 pounds per square inch

#### Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### **Screw Material:**

Steel comp 4037 or steel comp 8630

#### Screw Material Specification:

Ams 6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response

#### Screw Surface Treatment:

Cadmium and chromate

### Screw Surface Treatment Specification:

Qq-a-416, type 2, class 3 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

## **Specification Data:**

80205-nas514 professional/industrial association standard

### Shelf Life:

N/a

## Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5305-00-822-4523

Machine Screw - Page 2 of 2

**Fiig:** A500d0

Mil-std (military Standard):

Mil-s-6050 spec.

