NSN 5305-00-822-5083

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-822-5083

Through Observ
Thread Class:
3a The a Direction
Thread Direction:
Right-hand Three did a settle
Thread Length:
Between 0.372 inches and 0.510 inches
Fastener Length:
Between 1.015 inches and 1.062 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.502 inches and 0.507 inches
Shoulder Diameter:
0.264 inches first shoulder and 0.265 inches first shoulder
Shoulder Length:
0.450 inches first shoulder and 0.472 inches first shoulder
Internal Drive Style:
High-torque
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
100.0 degrees
Shoulder Shape:
Round first shoulder
Material:
Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4140 or steel comp
4037 or steel comp 4130
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2, cl 3 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5305-00-822-5083

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0