## NSN 5305-00-822-6072

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-822-6072

| Thread Class:   |
|---|
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| 0.500 inches  |
| Fastener Length:  |
| Between 1.495 inches and 1.505 inches                       |
| Head Style:   |
| Flat chamfer  |
| Head Diameter:  |
| Between 0.543 inches and 0.552 inches                       |
| Head Height:  |
| Between 0.244 inches and 0.250 inches                       |
| Shoulder Diameter:  |
| 0.371 inches first shoulder and 0.373 inches first shoulder |
| Shoulder Length:  |
| 0.995 inches first shoulder and 1.005 inches first shoulder |
| Internal Drive Style:                                       |
| Hexagon   |
| Thread Diameter:  |
| 0.312 inches  |
| Thready Qty Per Inch (tpi):                                 |
| 18  |
| Min. Tensile Strength (psi):                                |
| 160000 pounds per square inch                               |
| Hardness Rating:  |
| 36.0 rockwell c and 40.0 rockwell c                         |
| Shoulder Shape:   |
| Round first shoulder  |
| Material:   |
| Stainless steel   |
| Surface Treatment:  |
| Passivate   |
| Thread Series Designator:                                   |
| Unc   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
|   |

## NSN 5305-00-822-6072

Shoulder Screw - Page 2 of 2

Fiig: A003b0

