NSN 5305-00-823-5837

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-823-5837 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.312 inches **Fastener Length:** Between 0.656 inches and 0.688 inches **Head Style:** Fillister **Head Diameter:** Between 0.292 inches and 0.313 inches **Head Height:** Between 0.123 inches and 0.130 inches **First Diameter From Head:** Between 0.129 inches and 0.134 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.359 inches and 0.391 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 60000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel **Material Specification:** Astm a575 assn standard single material response or astm a576 assn standard single material response or astm a108 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 1 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life:

--

N/a

Unit Of Measure:

NSN 5305-00-823-5837

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0