

View Online at <https://aerobasegroup.com/nsn/5305-00-823-5902>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.359 inches and 0.391 inches

**Fastener Length:**

Between 1.940 inches and 1.950 inches

**Head Style:**

Knurled no. 1

**Head Diameter:**

Between 0.609 inches and 0.641 inches

**Head Height:**

Between 0.175 inches and 0.185 inches

**First Diameter From Head:**

Between 0.183 inches and 0.193 inches

**Second Diameter From Head:**

Between 0.155 inches and 0.165 inches

**Third Diameter From Head:**

Between 0.183 inches and 0.193 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.150 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

0.325 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

1.570 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Steel comp 1212

**Material Specification:**

Qq-s-637 federal specification single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification all treatment responses

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0