## NSN 5305-00-824-7362

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-824-7362 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.312 inches and 0.406 inches **Fastener Length:** 0.438 inches **Head Style:** Hexagon **Head Height:** Between 0.105 inches and 0.120 inches Width Between Flats: Between 0.302 inches and 0.313 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch **Hardness Rating:** Between 26.0 rockwell c and 32.0 rockwell c **Screw Material:** Steel comp 8630 **Screw Material Specification:** Mil-s-6050 military specification single material response or an-s-9 military standard single material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No Fiig:

A500d0

## NSN 5305-00-824-7362

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6050 spec.