Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-825-0289

| Thread Classe |
|----------------------------------------------------------------------|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.813 inches |
| Fastener Length: |
| 1.250 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.218 inches and 0.226 inches |
| Head Height: |
| Between 0.134 inches and 0.138 inches |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.138 inches |
| Width Across Flats: |
| 0.109 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 180000 pounds per square inch |
| Hardness Rating: |
| 38.0 rockwell c and 45.0 rockwell c |
| Minimum Yield Strength: |
| 155000 pounds per square inch |
| Surface Finish: |
| 63.0 microinches grip |
| Material: |
| Steel |
| Material Specification: |
| 66 federal standard single material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, type 2, cl 3 federal specification all treatment responses |
| Thread Series Designator: |
| Unc |
| Specification Or Standard: |
| 6 type |
| |

NSN 5305-00-825-0289

Socket Head Cap Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

