# NSN 5305-00-825-6759

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-825-6759



## **Thread Class:** 3a

**Thread Direction:** 

Right-hand

### Thread Length:

Between 0.608 inches and 0.749 inches

#### Fastener Length:

Between 0.734 inches and 0.781 inches

#### Head Style:

Hexagon

Head Height:

Between 0.096 inches and 0.110 inches

#### Width Between Flats:

Between 0.241 inches and 0.250 inches

#### Internal Drive Style:

Cross recess type 1

#### Thread Diameter:

0.164 inches

#### Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

125000 pounds per square inch

#### Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

#### Screw Material:

Steel comp 8630

#### Screw Material Specification:

Mil-s-6050 military specification single material response or an-s-9 military standard single material response

#### Screw Surface Treatment:

Cadmium

#### Screw Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment response

#### **Thread Series Designator:**

Unc

#### Shelf Life:

N/a

#### Unit Of Measure:

---

### Demilitarization:

No

Fiig:

A500d0

# NSN 5305-00-825-6759

Machine Screw - Page 2 of 2

## Mil-std (military Standard):

Mil-s-6050 spec.

