NSN 5305-00-826-2438

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-826-2438 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.399 inches and 0.449 inches **Fastener Length:** Between 2.097 inches and 2.127 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.390 inches and 0.395 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.086 inches first hole **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.678 inches and 1.698 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** 100.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 1.991 inches first hole and 2.001 inches first hole **Product Name:** Navy special project Material: Steel comp 4130 **Surface Treatment:** Cadmium **Thread Series Designator:**

Unf

Shelf Life:

N/a

NSN 5305-00-826-2438

Close Tolerance Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0