## NSN 5305-00-826-3065

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-826-3065



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.314 inches and 0.451 inches

## Fastener Length:

Between 3.641 inches and 3.686 inches

#### **Head Style:**

Flat countersunk

#### Head Diameter:

Between 0.337 inches and 0.387 inches

## Internal Drive Style:

Cross recess type 1

## Thread Diameter:

0.190 inches

## Thready Qty Per Inch (tpi):

32

## Min. Tensile Strength (psi):

160000 pounds per square inch

## Hardness Rating:

Between 36.0 rockwell c and 40.0 rockwell c

## **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### **Screw Material:**

Steel comp 8630

## Screw Material Specification:

Mil-s-6050 military specification single material response or an-s-9 military standard single material response

## Screw Surface Treatment:

Cadmium and chromate

## Screw Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

## **Thread Series Designator:**

Unf

#### Shelf Life:

N/a

## Unit Of Measure:

--

### Demilitarization:

No

## Fiig:

A500d0

# NSN 5305-00-826-3065

Machine Screw - Page 2 of 2

## Mil-std (military Standard):

Mil-s-6050 spec.

