## NSN 5305-00-826-5321

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-826-5321 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.400 inches and 0.450 inches **Fastener Length:** Between 0.785 inches and 0.815 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.389 inches and 0.394 inches **Internal Drive Style:** Cross recess type ii **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 4130 **Screw Material Specification:** Mil-s-6758 military specification single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2class 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A500d0

## NSN 5305-00-826-5321

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.