## NSN 5305-00-827-2471

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-827-2471 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.148 inches **Fastener Length:** Between 0.200 inches and 0.220 inches **Head Style:** Fillister **Head Diameter:** Between 0.310 inches and 0.320 inches **Head Height:** Between 0.160 inches and 0.180 inches **Hole Diameter:** 0.062 inches First Diameter From Head: Between 0.175 inches and 0.195 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.052 inches and 0.072 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches **Hole Quantity:** 1 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 28 Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Hole Configuration Style:** Round longitudinal hole **Externally Relieved Body Diameter Quantity:** Material: Steel comp 8740 **Surface Treatment:** Cadmium **Thread Series Designator:** 

Unjf

## NSN 5305-00-827-2471

Externally Relieved Body Screw - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0