NSN 5305-00-827-5634

Shoulder Screw - Page 1 of 1

AUTU

View Online at https://aerobasegroup.com/nsn/5305-00-827-5634

Thread Class: 2a Thread Direction: Right-hand Thread Length: Between 0.316 inches and 0.351 inches Fastener Length: Between 0.672 inches and 0.703 inches Head Style: Pan no. 2 Head Diameter: Between 0.344 inches and 0.375 inches Head Height:

Between 0.070 inches and 0.075 inches

Shoulder Diameter:

0.248 inches first shoulder and 0.249 inches first shoulder

Shoulder Length:

0.352 inches first shoulder and 0.356 inches first shoulder

Internal Drive Style:

Slot

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Shoulder Shape:

Round first shoulder

Material:

Steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022 or steel comp 1025

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0