NSN 5305-00-827-6035

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-827-6035 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** Between 0.620 inches and 0.640 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.370 inches and 0.380 inches **Head Height:** Between 0.100 inches and 0.140 inches **First Diameter From Head:** Between 0.260 inches and 0.270 inches **Second Diameter From Head:** Between 0.135 inches and 0.145 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.150 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.260 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 or steel comp 303se **Material Specification:** Astm a582 assn standard 1st material response or mil-s-18732 military specification 2nd material response **Surface Treatment: Passivate Thread Series Designator:** Unf Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-00-827-6035

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-18732 spec.