## NSN 5305-00-827-9896

Setscrew - Page 1 of 2

**Thread Class:** 



View Online at https://aerobasegroup.com/nsn/5305-00-827-9896

3a
Thread Direction:
Right-hand
Thread Length:
0.580 inches
Fastener Length:
Between 0.740 inches and 0.750 inches
Head Style:
Hexagon
Head Height:
0.281 inches
Width Between Flats:
Between 0.490 inches and 0.502 inches
Hole Diameter:
Between 0.070 inches and 0.080 inches
Point Length:
0.165 inches
Point Diameter:
0.247 inches
Point Style:
Dog
Internal Drive Style:
W/o internal drive
Thread Diameter:
0.312 inches
Hole Quantity:
3
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Hole Configuration Style:
Hexagon corners
Material:
Steel comp 4037 or steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740 or steel comp 4140

## NSN 5305-00-827-9896

Setscrew - Page 2 of 2

Fiig: A003b0

Mil-std (military Standard):

Mil-b-6812 spec.



Material Specification:
Mil-b-6812 military specification all material responses
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 ty2 cl3 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No