NSN 5305-00-828-4595

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-828-4595

Thread Class: 3a Thread Direction: Right-hand Thread Length: 1.312 inches Fastener Length: 2.625 inches Head Style: Flat chamfer Head Diameter: Between 0.265 inches and 0.270 inches Head Height: Between 0.160 inches and 0.164 inches Internal Drive Style: Hexagon Thread Diameter: 0.164 inches Width Across Flats:
Thread Direction:Right-handThread Length:1.312 inchesFastener Length:2.625 inchesHead Style:Flat chamferHead Diameter:Between 0.265 inches and 0.270 inchesHead Height:Between 0.160 inches and 0.164 inchesInternal Drive Style:HexagonThread Diameter:0.164 inches
Right-handThread Length:1.312 inchesFastener Length:2.625 inchesHead Style:Flat chamferHead Diameter:Between 0.265 inches and 0.270 inchesHead Height:Between 0.160 inches and 0.164 inchesInternal Drive Style:HexagonThread Diameter:0.164 inches
Thread Length:1.312 inchesFastener Length:2.625 inchesHead Style:Flat chamferHead Diameter:Between 0.265 inches and 0.270 inchesHead Height:Between 0.160 inches and 0.164 inchesInternal Drive Style:HexagonThread Diameter:0.164 inches
1.312 inches Fastener Length: 2.625 inches Head Style: Flat chamfer Head Diameter: Between 0.265 inches and 0.270 inches Head Height: Between 0.160 inches and 0.164 inches Internal Drive Style: Hexagon Thread Diameter: 0.164 inches
Fastener Length:2.625 inchesHead Style:Flat chamferHead Diameter:Between 0.265 inches and 0.270 inchesHead Height:Between 0.160 inches and 0.164 inchesInternal Drive Style:HexagonThread Diameter:0.164 inches
2.625 inches Head Style: Flat chamfer Head Diameter: Between 0.265 inches and 0.270 inches Head Height: Between 0.160 inches and 0.164 inches Internal Drive Style: Hexagon Thread Diameter: 0.164 inches
Head Style: Flat chamfer Head Diameter: Between 0.265 inches and 0.270 inches Head Height: Between 0.160 inches and 0.164 inches Internal Drive Style: Hexagon Thread Diameter: 0.164 inches
Flat chamfer Head Diameter: Between 0.265 inches and 0.270 inches Head Height: Between 0.160 inches and 0.164 inches Internal Drive Style: Hexagon Thread Diameter: 0.164 inches
Head Diameter: Between 0.265 inches and 0.270 inches Head Height: Between 0.160 inches and 0.164 inches Internal Drive Style: Hexagon Thread Diameter: 0.164 inches
Between 0.265 inches and 0.270 inches Head Height: Between 0.160 inches and 0.164 inches Internal Drive Style: Hexagon Thread Diameter: 0.164 inches
Head Height: Between 0.160 inches and 0.164 inches Internal Drive Style: Hexagon Thread Diameter: 0.164 inches
Between 0.160 inches and 0.164 inches Internal Drive Style: Hexagon Thread Diameter: 0.164 inches
Internal Drive Style: Hexagon Thread Diameter: 0.164 inches
Hexagon Thread Diameter: 0.164 inches
Thread Diameter: 0.164 inches
0.164 inches
Width Across Flats:
Between 0.125 inches and 0.127 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 43.0 rockwell c
Minimum Yield Strength:
130000 pounds per square inch
Material:
Steel
Surface Treatment:
Chromate zinc
Thread Series Designator:
Unc
Specification Or Standard:
1 type
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5305-00-828-4595

Socket Head Cap Screw - Page 2 of 2

Fiig: A003b0

