

View Online at <https://aerobasegroup.com/nsn/5305-00-832-6344>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.156 inches and 1.218 inches

**Fastener Length:**

Between 2.469 inches and 2.531 inches

**Head Style:**

Hexagon

**Head Height:**

0.281 inches

**Width Between Flats:**

0.562 inches

**Shank Unthreaded Hole Diameter:**

0.094 inches first hole and 0.156 inches first hole

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.203 inches first hole and 2.297 inches first hole

**Material:**

Steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022 or steel comp 1025

**Surface Treatment:**

Cadmium and zinc

**Surface Treatment Specification:**

Qq-p-416 type 1 class 2 federal specification 1st treatment response or qq-z-325 type 1 class 1 federal specification 2nd treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0