NSN 5305-00-832-6609

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-832-6609

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.547 inches and 0.641 inches
Fastener Length: Between 0.609 inches and 0.641 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.303 inches and 0.312 inches
Head Height:
Between 0.185 inches and 0.190 inches
Locking Feature:
Pellet threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.190 inches
Width Across Flats:
0.156 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
130000 pounds per square inch
Special Features:
Supplementary oil treatment of mil-l-644
Material:
Steel
Material Specification:
66 federal standard single material response
Surface Treatment:
Phosphate manganese
Surface Treatment Specification:
Mil-p-16232 type m class 1 military specification single treatment response
Thread Series Designator:

Unf

NSN 5305-00-832-6609

Socket Head Cap Screw - Page 2 of 2



Specification Or Standard:
6 type
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
No Fiig:

Mil-std (military Standard):

Mil-p-16232 spec.