

View Online at <https://aerobasegroup.com/nsn/5305-00-833-3417>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.553 inches and 0.603 inches

Fastener Length:

Between 0.938 inches and 0.968 inches

Head Style:

Pan

Head Diameter:

Between 0.611 inches and 0.740 inches

Head Height:

Between 0.244 inches and 0.261 inches

Locking Feature:

Patch threads or pellet threads or strip threads

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.375 inches

Grip Length:

Between 0.365 inches and 0.385 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Surface Finish:

32.0 microinches threads

Material:

Steel comp e4340 fastener or steel comp 4140 fastener or steel comp 8740 fastener or steel comp 8735 fastener or steel comp 6150 fastener

Surface Treatment:

Cadmium fastener and chromate fastener

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response fastener

Thread Series Designator:

Unjf

Specification Data:

80205-nas1176 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0