NSN 5305-00-834-6168

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-834-6168



Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.762 inches and 0.812 inches

Fastener Length:

Between 0.781 inches and 0.812 inches

Head Style:

Pan

Head Diameter:

Between 0.205 inches and 0.219 inches

Head Height:

Between 0.070 inches and 0.080 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

Between 36.0 rockwell c and 40.0 rockwell c

Screw Material:

Steel comp 8630

Screw Material Specification:

Mil-s-6050 military specification single material response or an-s-9 military standard single material response

Screw Surface Treatment:

Cadmium

Screw Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A500d0

NSN 5305-00-834-6168

Machine Screw - Page 2 of 2

Mil-std (military Standard):

Mil-s-6050 spec.

