NSN 5305-00-835-2103

Socket Head Cap Screw - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5305-00-835-2103



Thread Class: 3a Thread Direction: Right-hand Thread Length: 0.344 inches Fastener Length: 0.344 inches Head Style: Binding Head Diameter: Between 0.223 inches and 0.235 inches Head Height: Between 0.056 inches and 0.068 inches Locking Feature: Patch threads or strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:	
Thread Direction: Right-hand Thread Length: 0.344 inches Fastener Length: 0.344 inches Head Style: Binding Head Diameter: Between 0.223 inches and 0.235 inches Head Height: Between 0.056 inches and 0.068 inches Locking Feature: Patch threads or strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	Thread Class:
Right-hand Thread Length: 0.344 inches Fastener Length: 0.344 inches Head Style: Binding Head Diameter: Between 0.223 inches and 0.235 inches Head Height: Between 0.056 inches and 0.068 inches Locking Feature: Patch threads or strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	3a
Thread Length: 0.344 inches Fastener Length: 0.344 inches Head Style: Binding Head Diameter: Between 0.223 inches and 0.235 inches Head Height: Between 0.056 inches and 0.068 inches Locking Feature: Patch threads or strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	Thread Direction:
Co.344 inches Fastener Length: 0.344 inches Head Style: Binding Head Diameter: Between 0.223 inches and 0.235 inches Head Height: Between 0.056 inches and 0.068 inches Locking Feature: Patch threads or strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	Right-hand
Fastener Length: 0.344 inches Head Style: Binding Head Diameter: Between 0.223 inches and 0.235 inches Head Height: Between 0.056 inches and 0.068 inches Locking Feature: Patch threads or strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	Thread Length:
Head Style: Binding Head Diameter: Between 0.223 inches and 0.235 inches Head Height: Between 0.056 inches and 0.068 inches Locking Feature: Patch threads or strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	0.344 inches
Head Style: Binding Head Diameter: Between 0.223 inches and 0.235 inches Head Height: Between 0.056 inches and 0.068 inches Locking Feature: Patch threads or strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	Fastener Length:
Binding Head Diameter: Between 0.223 inches and 0.235 inches Head Height: Between 0.056 inches and 0.068 inches Locking Feature: Patch threads or strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	0.344 inches
Head Diameter: Between 0.223 inches and 0.235 inches Head Height: Between 0.056 inches and 0.068 inches Locking Feature: Patch threads or strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	Head Style:
Between 0.223 inches and 0.235 inches Head Height: Between 0.056 inches and 0.068 inches Locking Feature: Patch threads or strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	Binding
Head Height: Between 0.056 inches and 0.068 inches Locking Feature: Patch threads or strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	Head Diameter:
Between 0.056 inches and 0.068 inches Locking Feature: Patch threads or strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	Between 0.223 inches and 0.235 inches
Locking Feature: Patch threads or strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	Head Height:
Patch threads or strip threads Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	Between 0.056 inches and 0.068 inches
Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	Locking Feature:
Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	Patch threads or strip threads
Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	Internal Drive Style:
0.112 inches Thready Qty Per Inch (tpi): 40 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	Cross recess type 1
Thready Qty Per Inch (tpi): 40 Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	Thread Diameter:
Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	0.112 inches
Material: Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	Thready Qty Per Inch (tpi):
Stainless steel Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	40
Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	Material:
Passivate Thread Series Designator: Unc Shelf Life: N/a	Stainless steel
Thread Series Designator: Unc Shelf Life: N/a	Surface Treatment:
Unc Shelf Life: N/a	Passivate
Shelf Life: N/a	Thread Series Designator:
N/a	Unc
. 40	Shelf Life:
Unit Of Measure:	N/a
	Unit Of Measure:
Demilitarization:	Demilitarization:
No	No
Fiig:	Fiig:
A003b0	A003b0