NSN 5305-00-835-6884

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-835-6884 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.236 inches and 0.267 inches **Fastener Length:** Between 0.281 inches and 0.312 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.058 inches and 0.068 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Secondary Washer Relationship To Primary Washer: Not identical **Primary Washer Outside Diameter:** Between 0.245 inches and 0.255 inches **Secondary Washer Outside Diameter:** Between 0.226 inches and 0.236 inches **Primary Washer Style:** Flat **Primary Washer Material Thickness:** 0.030 inches **Secondary Washer Material Thickness:** 0.015 inches Material: Steel comp 430 **Material Specification:** Qq-s-763 cond a federal specification single material response **Surface Treatment:**

Passivate

Surface Treatment Specification:

Mil-f-14072 military specification single treatment response

NSN 5305-00-835-6884

Assembled Washer Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0

Mil-std (military Standard):

Mil-f-14072 spec.