NSN 5305-00-835-9309

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-835-9309

Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 0.464 inches and 0.625 inches **Fastener Length:** Between 2.219 inches and 2.266 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.569 inches and 0.635 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 8630 **Screw Material Specification:** Mil-s-6050 military specification single material response or an-s-9 military standard single material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unf **Departure From Cited Designator:** As modified by internal drive style and location Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-00-835-9309

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.