## NSN 5305-00-835-9657



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-835-9657 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.372 inches and 0.510 inches **Fastener Length:** Between 1.203 inches and 1.250 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.464 inches and 0.506 inches **Shoulder Diameter:** 0.264 inches first shoulder and 0.265 inches first shoulder **Shoulder Length:** 0.638 inches first shoulder and 0.660 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** 100.0 degrees **Shoulder Shape:** Round first shoulder

Material:

Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4140 or steel comp

4037 or steel comp 4130

**Surface Treatment:** Cadmium and chromate

**Surface Treatment Specification:** 

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5305-00-835-9657

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0