## NSN 5305-00-836-3911

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-836-3911 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.495 inches and 0.602 inches **Fastener Length:** 0.625 inches **Head Style:** Round **Head Diameter:** Between 0.443 inches and 0.472 inches **Head Height:** Between 0.160 inches and 0.175 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Hardness Rating:** 40.0 rockwell c primary washer and 50.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.460 inches and 0.475 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** Between 0.023 inches and 0.028 inches Material: Steel comp 1010 or steel comp 1011 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1050 or steel comp 1551 or steel comp 1059 or steel comp 1060 or steel comp 1561 or steel comp 1566 **Surface Treatment:** Cadmium or zinc **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response **Thread Series Designator:** Unf Shelf Life:

--

N/a

**Unit Of Measure:** 

## NSN 5305-00-836-3911

Assembled Washer Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0