NSN 5305-00-837-8452

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-837-8452

| Thread Class: | |
|-------------------------|---|
| 3a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| Between 0.372 inches | and 0.510 inches |
| Fastener Length: | |
| Between 1.765 inches | and 1.812 inches |
| Head Style: | |
| Flat countersunk | |
| Head Diameter: | |
| Between 0.502 inches | and 0.507 inches |
| Shoulder Diameter: | |
| 0.280 inches first shou | lder and 0.281 inches first shoulder |
| Shoulder Length: | |
| 1.207 inches first shou | lder and 1.229 inches first shoulder |
| Internal Drive Style: | |
| High-torque | |
| Thread Diameter: | |
| 0.250 inches | |
| Thready Qty Per Inch | (tpi): |
| 28 | |
| Min. Tensile Strength | (psi): |
| 160000 pounds per squ | lare inch |
| Hardness Rating: | |
| 36.0 rockwell c and 40 |).0 rockwell c |
| Countersink Angle: | |
| 100.0 degrees | |
| Shoulder Shape: | |
| Round first shoulder | |
| Material: | |
| Steel comp e4340 or s | teel comp 4340 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4140 or steel com |
| 4037 or steel comp 41 | 30 |
| Surface Treatment: | |
| Cadmium and chromat | e |
| Surface Treatment Sp | ecification: |
| | ederal specification single treatment response |
| Thread Series Design | |
| Unf | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |

NSN 5305-00-837-8452

Shoulder Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

