NSN 5305-00-837-8454



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-837-8454 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.372 inches and 0.510 inches **Fastener Length:** Between 1.265 inches and 1.312 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.502 inches and 0.507 inches **Shoulder Diameter:** 0.280 inches first shoulder and 0.281 inches first shoulder **Shoulder Length:** 0.707 inches first shoulder and 0.729 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** 100.0 degrees **Shoulder Shape:** Round first shoulder Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4140 or steel comp 4037 or steel comp 4130

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

NSN 5305-00-837-8454

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0