## NSN 5305-00-838-1386

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-838-1386 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.570 inches and 0.626 inches **Fastener Length:** Between 0.691 inches and 0.693 inches **Head Style:** Hexagon **Head Height:** Between 0.057 inches and 0.067 inches Width Between Flats: 0.500 inches **Shoulder Diameter:** 0.184 inches first shoulder and 0.188 inches first shoulder **Shoulder Length:** 0.067 inches first shoulder and 0.071 inches first shoulder **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Shoulder Shape:** Round first shoulder **Product Name:** Navy special project Material: Steel comp 303 **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924, cl 3 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5305-00-838-1386

Shoulder Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.