NSN 5305-00-838-5988

Machine Screw - Page 1 of 2

Thread Class:

View Online at https://aerobasegroup.com/nsn/5305-00-838-5988



3a **Thread Direction: Right-hand Thread Length:** Between 0.377 inches and 0.516 inches Fastener Length: Between 2.079 inches and 2.126 inches **Head Style:** Round **Head Diameter:** Between 0.361 inches and 0.385 inches **Head Height:** Between 0.103 inches and 0.118 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 248.0 brinell standard and 321.0 brinell standard **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams 5735 assn standard single material response **Screw Surface Treatment:** Passivate **Screw Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A500d0

NSN 5305-00-838-5988

Machine Screw - Page 2 of 2

Mil-std (military Standard):

Mil-s-5002 spec.

