

View Online at <https://aerobasegroup.com/nsn/5305-00-838-9396>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.250 inches and 1.440 inches

**Fastener Length:**

2.000 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.302 inches and 0.323 inches

**Width Between Flats:**

Between 0.736 inches and 0.750 inches

**Thread Diameter:**

0.500 inches

**Thready Qty Per Inch (tpi):**

13

**Min. Tensile Strength (psi):**

120000 pounds per square inch

**Hardness Rating:**

23.0 rockwell c and 32.0 rockwell c

**Minimum Yield Strength:**

85000 pounds per square inch

**Product Name:**

Screw, cap, hexagon head

**Material:**

Steel comp 1020

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 class 3 federal specification single treatment response

**Thread Series Designator:**

Unc

**Specification Or Standard:**

2 type and 10p style

**Departure From Cited Designator:**

As modified by material and class of thread

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0