Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-839-4297

Thread Direction: Right-hand Thread Length: 0.390 inches Fastener Length: Between 0.790 inches and 0.830 inches Head Style: Fillister Head Style: Fillister Head Diameter: Between 0.250 inches and 0.270 inches Head Height: Between 0.250 inches and 0.113 inches First Diameter From Head: 0.114 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.300 inches and 0.420 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thread V P Pr Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Qq=-r63 federal specification single material response Surface Treatment: Passivate Thread Series Designator: Unc Sheft Life: N/a Unit Of Measure: - <th>Thread Class:</th>	Thread Class:
Tread Direction: Right-hand Thread Length: 0.390 inches Fastener Length: Between 0.790 inches and 0.830 inches Head Style: Fillister Head Diameter: Between 0.250 inches and 0.270 inches Head Height: Between 0.250 inches and 0.270 inches Head Height: Between 0.106 inches and 0.113 inches First Diameter From Head: 0.114 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.380 inches and 0.420 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thread Diameter: 0.164 inches Thread Diameter: 0.164 inches Thread Diameter: 0.164 inches Thread Diameter: 0.164 inches Thread Style: Cross recess type 1 Thread Style: Thread Style: Thread Style: Thread Style: Na Unic Of Measure: Demilitarization: No Fig:	
Right-hand Thread Length: 0.390 inches Fastener Length: Between 0.790 inches and 0.830 inches Head Style: Fillister Head Diameter: Between 0.250 inches and 0.270 inches Head Height: Between 0.260 inches and 0.270 inches Head Height: Between 0.106 inches and 0.113 inches First Diameter From Head: 0.114 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.380 inches and 0.420 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thread Vaty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification Qq-s-763 federal specification single material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Tread Length: 0.390 inches Fastener Length: Between 0.790 inches and 0.830 inches Head Style: Fillister Head Diameter: Between 0.250 inches and 0.270 inches Head Height: Between 0.106 inches and 0.113 inches First Diameter From Head: 0.114 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.380 inches and 0.420 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thread Diameter: 0.164 inches Thread Vaty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	
0.390 inches Fastener Length: Between 0.790 inches and 0.830 inches Head Style: Fillister Head Diameter: Between 0.250 inches and 0.270 inches Head Height: Between 0.250 inches and 0.270 inches Head Height: Between 0.106 inches and 0.113 inches First Diameter From Head: 0.114 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.380 inches and 0.420 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thread Diameter: 1 Material: Steel comp 303 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Fastener Length: Between 0.790 inches and 0.830 inches Head Style: Fillister Head Diameter: Between 0.250 inches and 0.270 inches Head Height: Between 0.106 inches and 0.113 inches First Diameter From Head: 0.114 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.380 inches and 0.420 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Stel comp 303 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Between 0.790 inches and 0.830 inches Head Style: Fillister Head Diameter: Between 0.250 inches and 0.270 inches Head Height: Between 0.106 inches and 0.113 inches First Diameter From Head: 0.114 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.380 inches and 0.420 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thread Diameter: 0.164 inches Thread Vay Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Head Style: Fillister Head Diameter: Between 0.250 inches and 0.270 inches Head Height: Between 0.106 inches and 0.113 inches First Diameter From Head: 0.114 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.380 inches and 0.420 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	-
Filister Head Diameter: Between 0.250 inches and 0.270 inches Head Height: Between 0.106 inches and 0.113 inches First Diameter From Head: 0.114 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.380 inches and 0.420 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Head Diameter: Between 0.250 inches and 0.270 inches Head Height: Between 0.106 inches and 0.113 inches First Diameter From Head: 0.114 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.380 inches and 0.420 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thread Yap Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Between 0.250 inches and 0.270 inches Head Height: Between 0.106 inches and 0.113 inches First Diameter From Head: 0.114 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.380 inches and 0.420 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Thread Series Designator: Unc Sheff Life: N/a Unit Of Measure: Demilitarization: No Filg:	
Head Height: Between 0.106 inches and 0.113 inches First Diameter From Head: 0.114 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.380 inches and 0.420 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Between 0.106 inches and 0.113 inches First Diameter From Head: 0.114 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.380 inches and 0.420 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
First Diameter From Head: 0.114 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.380 inches and 0.420 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
0.114 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.380 inches and 0.420 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.380 inches and 0.420 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Between 0.380 inches and 0.420 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
0.164 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
32 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 303 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	
1 Material: Steel comp 303 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Material: Steel comp 303 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Steel comp 303 Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Material Specification: Qq-s-763 federal specification single material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Qq-s-763 federal specification single material response Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-
Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-
Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
N/a Unit Of Measure: Demilitarization: No Fiig:	
Unit Of Measure: Demilitarization: No Fiig:	
 Demilitarization: No Fiig:	
No Fiig:	
No Fiig:	Demilitarization:
Fiig:	