

View Online at <https://aerobasegroup.com/nsn/5305-00-840-3538>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.255 inches and 0.322 inches

Fastener Length:

Between 0.550 inches and 0.597 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.451 inches and 0.483 inches

Grip Diameter:

Between 0.2485 inches and 0.2495 inches

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.250 inches

Grip Length:

Between 0.240 inches and 0.260 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

180000 pounds per square inch

Countersink Angle:

100.0 degrees

Surface Finish:

32.0 microinches grip

Material:

Steel

Material Specification:

Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response or mil-s-6050 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.