## NSN 5305-00-840-5299

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-840-5299

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.563 inches and 0.625 inches
Fastener Length:
0.625 inches
Head Style:
Pan
Head Diameter:
Between 0.306 inches and 0.322 inches
Head Height:
Between 0.105 inches and 0.115 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.164 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Between 36.0 rockwell c and 40.0 rockwell c
Screw Material:
Steel comp 8630
Screw Material Specification:
Mil-s-6050 military specification single material response or an-s-9 military standard single material response
Bearing Surface Of Head Surface Treatment:
Cadmium
Screw Surface Treatment Specification:
Qq-p-416, type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unc
Specification Data:
80205-nas602 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5305-00-840-5299

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.