NSN 5305-00-840-9661

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-840-9661 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.313 inches and 0.363 inches **Fastener Length:** Between 0.573 inches and 0.603 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.297 inches and 0.302 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 4130 **Screw Material Specification:** Mil-s-6758 military specification single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq -p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unf

Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A500d0

NSN 5305-00-840-9661

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6758 spec.