
## NSN 5305-00-841-1276

Machine Screw - Page 1 of 2

**Thread Class:** 

**Thread Direction:** 

3a





## **Right-hand Thread Length:** 0.531 inches **Fastener Length:** Between 0.641 inches and 0.686 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.572 inches and 0.638 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 4037 or steel comp 8630 **Screw Material Specification:** Ams 6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-b-416, type 2, cl 3 federal specification all treatment responses **Thread Series Designator:** Unf **Specification Data:** 80205-nas517 professional/industrial association standard Shelf Life: N/a Unit Of Measure: ---

## **Demilitarization:**

No

## NSN 5305-00-841-1276

Machine Screw - Page 2 of 2

**Fiig:** A500d0

Mil-std (military Standard):

Mil-s-6050 spec.

