NSN 5305-00-841-2942



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-841-2942 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.450 inches and 0.500 inches **Fastener Length:** 0.500 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:**

Between 36.0 rockwell c and 40.0 rockwell c

Screw Material:

Steel comp 8630

Screw Material Specification:

Mil-s-6050 military specification single material response or an-s-9 military standard single material response

Screw Surface Treatment:

Cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416, type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unc

Specification Data:

80205-nas600 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5305-00-841-2942

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.