## NSN 5305-00-842-1583

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-842-1583 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.270 inches **Fastener Length:** Between 1.938 inches and 1.978 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.3737 inches and 0.3742 inches **Head Height:** 0.263 inches **Grip Diameter:** Between 0.2487 inches and 0.2492 inches **Shank Unthreaded Hole Diameter:** 0.076 inches all holes and 0.086 inches all holes **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.500 inches and 1.520 inches Width Across Flats: Between 0.1875 inches and 0.1900 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 2040 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 0.990 inches all holes and 0.119 inches all holes **Surface Finish:** 32.0 microinches threads **Special Features:** Two locking detents on the shank Material: Steel comp 440c **Thread Series Designator:** Unf Shelf Life:

N/a

## NSN 5305-00-842-1583

Close Tolerance Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0