NSN 5305-00-842-1583

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-842-1583

Thread Classy
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.270 inches
Fastener Length:
Between 1.938 inches and 1.978 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.3737 inches and 0.3742 inches
Head Height:
0.263 inches
Grip Diameter:
Between 0.2487 inches and 0.2492 inches
Shank Unthreaded Hole Diameter:
0.076 inches all holes and 0.086 inches all holes
Internal Drive Style:
Hexagon
Thread Diameter:
0.250 inches
Grip Length:
Between 1.500 inches and 1.520 inches
Width Across Flats:
Between 0.1875 inches and 0.1900 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
2040 pounds per square inch
Distance From Head Largest Bearing Surface To Shank Hole Center:
0.990 inches all holes and 0.119 inches all holes
Surface Finish:
32.0 microinches threads
Special Features:
Two locking detents on the shank
Material:
Steel comp 440c
Thread Series Designator:
Unf
Shelf Life:
N/a

NSN 5305-00-842-1583

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

