NSN 5305-00-842-1589

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-842-1589 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.290 inches **Fastener Length:** Between 2.250 inches and 2.290 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.3737 inches and 0.3742 inches **Head Height:** 0.263 inches **Grip Diameter:** Between 0.2487 inches and 0.2492 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.086 inches first hole **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.812 inches and 1.832 inches Width Across Flats: Between 0.187 inches and 0.190 inches Thready Qty Per Inch (tpi): 28 Distance From Head Largest Bearing Surface To Shank Hole Center: 2.141 inches first hole and 2.181 inches first hole **Special Features:** Retaining element in shank Material: Steel comp 630 or steel comp 440c or steel comp 631 **Material Specification:** 17-4ph fscm 81755 mfr ref 1st material response or qq-s-763 federal specification 2nd material response or ams 5673 assn standard 3rd material response **Thread Series Designator:** Unf Shelf Life:

--

N/a

Unit Of Measure:

NSN 5305-00-842-1589

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0