## NSN 5305-00-842-7565

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-842-7565

<b></b>	
	read Class:
3a 	
	read Direction:
	ght-hand
	read Length:
	tween 0.490 inches and 0.557 inches
	stener Length:
	tween 1.688 inches and 1.735 inches
	ad Style:
	at countersunk
	ad Diameter:
	tween 0.752 inches and 0.762 inches
	ip Diameter:
	tween 0.3735 inches and 0.3745 inches
	ernal Drive Style:
	gh-torque
	read Diameter:
	375 inches
	ip Length:
	tween 1.178 inches and 1.198 inches
	ready Qty Per Inch (tpi):
24	
	n. Tensile Strength (psi):
	0000 pounds per square inch
	rdness Rating:
	.0 rockwell c and 50.0 rockwell c
	buntersink Angle:
	tween 99.0 degrees and 101.0 degrees
	eel comp h11
	aterial Specification: ns 6487 assn standard single material response
	is 6467 assit standard single material response
	Indee Treatment.
	Inface Treatment Specification:
	ac ps13145 fscm 76301 mfr ref single treatment response
	read Series Designator:
Un	-
	یں elf Life:
N/a	
	a nit Of Measure:

## NSN 5305-00-842-7565

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

