NSN 5305-00-842-7579

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-842-7579 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.573 inches and 0.640 inches **Fastener Length:** Between 1.958 inches and 2.005 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.880 inches and 0.890 inches **Grip Diameter:** Between 0.4360 inches and 0.4370 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.437 inches **Grip Length:** Between 1.365 inches and 1.385 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Navy special project Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mac ps13145 fscm 76301 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

NSN 5305-00-842-7579

Close Tolerance Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0