

View Online at <https://aerobasegroup.com/nsn/5305-00-843-6394>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 1.250 inches and 1.438 inches

Fastener Length:

Between 3.170 inches and 3.250 inches

Head Style:

Hexagon

Head Height:

Between 0.302 inches and 0.323 inches

Width Between Flats:

Between 0.736 inches and 0.750 inches

Shank Unthreaded Hole Diameter:

0.105 inches first hole and 0.113 inches first hole

Thread Diameter:

0.500 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

120000 pounds per square inch

Hardness Rating:

23.0 rockwell c and 32.0 rockwell c

Minimum Yield Strength:

85000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.068 inches first hole and 3.088 inches first hole

Material:

Steel

Material Specification:

Sae gr 5 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 federal specification all treatment responses

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0