NSN 5305-00-844-5911

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-844-5911

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.469 inches
Fastener Length:
2.594 inches
Head Style:
Knurled no. 1
Head Diameter:
0.562 inches
Head Height:
0.125 inches
First Diameter From Head:
0.025 inches
Second Diameter From Head:
0.016 inches
Third Diameter From Head:
0.230 inches
Fourth Diameter From Head:
0.187 inches
0.187 inches Fifth Diameter From Head:
Fifth Diameter From Head:
Fifth Diameter From Head: 0.230 inches
Fifth Diameter From Head: 0.230 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Fifth Diameter From Head: 0.230 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.437 inches
Fifth Diameter From Head: 0.230 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.437 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter:
Fifth Diameter From Head: 0.230 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.437 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.500 inches
Fifth Diameter From Head: 0.230 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.437 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.500 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter:
Fifth Diameter From Head: 0.230 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.437 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.500 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.562 inches
Fifth Diameter From Head: 0.230 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.437 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.500 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.562 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:
Fifth Diameter From Head: 0.230 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.437 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.500 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.562 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 2.062 inches
Fifth Diameter From Head: 0.230 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.437 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.500 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.562 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 2.062 inches Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter:
Fifth Diameter From Head: 0.230 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.437 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.500 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.562 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 2.062 inches Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter: 2.125 inches
Fifth Diameter From Head: 0.230 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.437 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.500 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.562 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 2.062 inches Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter: 2.125 inches Internal Drive Style:
Fifth Diameter From Head: 0.230 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.437 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.500 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.562 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 2.062 inches Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter: 2.125 inches Internal Drive Style: Cross recess type 1
Fifth Diameter From Head: 0.230 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.437 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.500 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.562 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 2.062 inches Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter: 2.125 inches Internal Drive Style: Cross recess type 1 Thread Diameter:

Externally Relieved Body Diameter Quantity:

NSN 5305-00-844-5911

Externally Relieved Body Screw - Page 2 of 2



Materiai:
Stainless steel
Surface Treatment:
Passivate
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0