

NSN 5305-00-844-5956 Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-844-5956 **Thread Class:** За **Thread Direction:** Right-hand

Thread Length: Between 0.204 inches and 0.240 inches **Fastener Length:**

Between 0.240 inches and 0.270 inches

Head Style: Flat chamfer

Between 0.136 inches and 0.140 inches

Head Height:

Between 0.083 inches and 0.086 inches

Hole Diameter:

0.037 inches

Hexagon

Head Diameter:

Internal Drive Style:

Thread Diameter:

0.086 inches

Width Across Flats:

Between 0.063 inches and 0.064 inches

Hole Quantity:

2

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

Min. Tensile Strength (psi):

75000 pounds per square inch

Hardness Rating:

80.0 rockwell b

Minimum Yield Strength:

30000 pounds per square inch

Hole Configuration Style:

Round internal hexagon

Material:

Steel comp 302 or steel comp 303 or steel comp 304

Material Specification:

Aisi assn standard all material responses

Surface Treatment:

Passivate

NSN 5305-00-844-5956

Socket Head Cap Screw - Page 2 of 2



Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Specification Data:

80205-nas608 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0