NSN 5305-00-844-7357

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-844-7357 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.213 inches and 0.218 inches **Fastener Length:** Between 0.529 inches and 0.534 inches **Head Style:** Pan **Head Diameter:** Between 0.245 inches and 0.260 inches **Head Height:** Between 0.086 inches and 0.091 inches **First Diameter From Head:** Between 0.125 inches and 0.130 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.316 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303se **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-00-844-7357

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.