NSN 5305-00-846-8869



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-846-8869 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.371 inches and 0.509 inches **Fastener Length:** Between 1.390 inches and 1.437 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.502 inches and 0.507 inches **Shoulder Diameter:** 0.264 inches first shoulder and 0.265 inches first shoulder **Shoulder Length:** 0.826 inches first shoulder and 0.848 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** 100.0 degrees **Shoulder Shape:** Round first shoulder Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4140 or steel comp 4037 or steel comp 4130 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:**

Unf

Shelf Life:

N/a

Unit Of Measure:

Thread Series Designator:

Qq-p-416, type 2, cl 3 federal specification single treatment response

NSN 5305-00-846-8869

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0