## NSN 5305-00-846-8871

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-846-8871 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.423 inches and 0.573 inches **Fastener Length:** Between 1.390 inches and 1.437 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.629 inches and 0.633 inches **Shoulder Diameter:** 0.327 inches first shoulder and 0.328 inches first shoulder **Shoulder Length:** 0.680 inches first shoulder and 0.702 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** 100.0 degrees **Shoulder Shape:** Round first shoulder Material: Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4140 or steel comp 4037 or steel comp 4130 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5305-00-846-8871

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0