NSN 5305-00-846-8872

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-846-8872 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.531 inches **Fastener Length:** Between 1.204 inches and 1.234 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.5780 inches and 0.6335 inches **Shoulder Diameter:** 0.327 inches first shoulder and 0.328 inches first shoulder **Shoulder Length:** 0.556 inches first shoulder and 0.578 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.3125 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, ty2, cl2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

Unit Of Measure:

NSN 5305-00-846-8872

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0