## NSN 5305-00-846-8890

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/psn/5305-00-846-8800

View Online at https://aerobasegroup.com/nsn/5305-00-846-8890
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.372 inches and 0.510 inches
Fastener Length:
Between 1.515 inches and 1.562 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.502 inches and 0.507 inches
Shoulder Diameter:
0.280 inches first shoulder and 0.281 inches first shoulder
Shoulder Length:
0.957 inches first shoulder and 0.979 inches first shoulder
Internal Drive Style:
High-torque
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
100.0 degrees
Shoulder Shape:
Round first shoulder
Material:
Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4140 or steel comp
4037 or steel comp 4130
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a

**Unit Of Measure:** 

## NSN 5305-00-846-8890

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0